

## 2150 / 2155 • For Decks, Siding & Fencing

**Product Description & Use:** Peel Away® Deck Stripper is a ready to use, biodegradable stripper for removing oil and water based stains, clear finishes, weathered latex and varnish from pine, oak, cedar, redwood and pressure treated decks, siding and fencing. Cedar and redwood may darken after using stripper. After stripping, we strongly recommend using Peel Away® Brightener and Neutralizer. **This product is available in Gallons and 5 Gallon Pails.**

**Limitations:** Product efficiency is greatly reduced when air and surface temperature is below 50° F.

**Test Area:** Test an inconspicuous area and allow drying thoroughly before general use.

**Coverage:** This product undiluted covers between 100-125 square feet per gallon. This product can be diluted at a ratio of 1:1 and will cover between 200-250 square feet per gallon.

**Application: To strip oil and water based stains, clear finishes, weathered latex and varnish:**

1. Apply diluted solution (see above for dilution) liberally with a plastic, pump style garden sprayer. On vertical surfaces, start from the bottom and work up. **DO NOT APPLY TO HOT SURFACES OR IN DIRECT SUNLIGHT.**
2. Allow stripper to stand approximately 5-15 minutes or until coating has softened or lifted. **DO NOT ALLOW STRIPPER TO DRY.** If stripper dries, mist with water or reapply stripper.
3. Agitate surface with a stiff brush or power washer to remove coating. **NOTE:** To avoid surface damage, if using a power washer, **DO NOT EXCEED 1000 PSI OR A 40 DEGREE TIP.** After coating is removed, thoroughly rinse surface and allow drying. Additional application may be necessary for complete removal of coating.
4. To brighten and neutralize the wood, we strongly recommend using the Peel Away® Brightener and

Neutralizer within 2-3 days after using the stripper. If Brightener and Neutralizer are not used, the high pH of the surface may cause premature failure of any future coatings.

5. Allow surface to dry thoroughly before applying a new finish. Lightly sanding the surface will help with penetration and adhesion of the new coatings.

**Dilution Guide:** Multiple coats of solid color paint or stain – **DO NOT DILUTE, USE FULL STRENGTH.**

Weathered solid color stain, paint, semi-transparent, transparent, and clear finishes – **DILUTE WITH 1 GALLON OF WATER TO 1 GALLON OF STRIPPER.**

**Health & Safety: CAUTION:** Wear safety goggles and/or face shield. Wear butyl gloves, impervious apron, boots and other clothing are recommended if needed, to prevent contact. If spraying (only outdoors), use a NIOSH approved organic vapor/dust mist respirator with appropriate eye protection. Do not mix or use with other household cleaners or chemicals. All surfaces must be thoroughly rinsed, dry and neutralized prior to staining or coating. Stripper residue will adversely affect stain or coating. Exercise caution when working on surfaces that are wet, especially from stripper. Wet surfaces are extremely slippery.

**DANGER: CORROSIVE LIQUID. KEEP OUT OF REACH OF CHILDREN.** CONTACT WITH EYES MAY CAUSE SEVERE BURNS WITH POSSIBLE CORNEA DAMAGE AND BLINDNESS. SKIN CONTACT MAY CAUSE CHEMICAL BURNS OR DERMATITIS IF EXPOSURE IS PROLONGED. VAPOR OF MIST MAY CAUSE IRRITATION TO EYES, MUCOUS MEMBRANES AND RESPIRATORY TRACT. INGESTION MAY CAUSE GASTROINTESTINAL CORROSION, VOMITTING, DIARRHEA, SHOCK OR DEATH. **Close container after each use. Use with adequate ventilation only. Wash thoroughly with soap and water after each use.**

**Warranty:** Dumond Chemicals, Inc. warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR

PURPOSE. Dumond Chemicals, Inc. liability shall be limited in all events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. Dumond Chemicals, Inc. shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of Dumond Chemicals, Inc. or its distributors, and dealers.

**Technical Services:** Dumond's expert staff is available to answer technical questions and provide product-specific information required by architects, specifiers, contractors and property owners. Expert, on-site assistance is available at no additional cost. Call 800-245-1191 or email [info@dumondglobal.com](mailto:info@dumondglobal.com) with product or technical questions.

## Technical Data

<b>Form:</b>	<b>Purple Viscous Liquid</b>
<b>Odor:</b>	<b>Mild</b>
<b>Wt. /Gal.:</b>	<b>10.0 lbs</b>
<b>Flash Point:</b>	<b>None</b>
<b>pH:</b>	<b>14</b>