

LIFT AWAY® GRAFFITI REMOVER SPECIFICATION AND DATA

PRODUCT NAME:

Lift Away Graffiti Remover

MANUFACTURER

Dumond Chemicals
104 Interchange Plaza, Ste. 202
Monroe Township, NJ 08831
Phone: 609-655-7700
Fax: 609-655-7725
Email: info@dumondglobal.com
Website: www.dumondchemicals.com

PRODUCT DESCRIPTION:

Lift Away® Graffiti Remover is a water based formulation which is biodegradable and environmentally safe. It has been designed specifically to simplify the graffiti removal process. This product will remove most types of graffiti and many stains from masonry, concrete, glass, terrazzo, metal and other surfaces. In most cases the entire removal process will be under fifteen (15) minutes. This product has a low odor. Coverage is about 150-250 square feet per gallon.

LIMITATIONS AND PREPARATORY WORK:

Product efficiency is reduced during cold weather. Surface and air temperature should be a minimum of 40° F during use of product. Test areas should be done that are typical of the surface being cleaned to ensure that the results will be satisfactory. This will also help the first time user of the product to gauge the time frame for removal.

APPLICATION:

Lift Away® Graffiti Remover should be brushed or sprayed onto the surface being cleaned. Allow several minutes for the product to work and then use a scrub brush to agitate the product on the surface to help the graffiti removal process. Clean up can be accomplished with a power washer (not to exceed 1200 psi) or a garden hose. Proper ventilation should be produced in confined areas. Collect residue and dispose of according to local and state regulations.

WE STRONGLY SUGGEST THAT AFTER CLEANING THE SURFACE OF GRAFFITI AN APPLICATION OF THE DUMOND ANTI GRAFFITI COATING BE USED. THIS IS A NON-SACRIFICIAL CLEAR COATING THAT WILL PROTECT THE SURFACE AND EASE THE REMOVAL OF ANY NEW GRAFFITI.

AVAILABILITY AND COST:

Watch Dog™ products are available through a nationwide network of paint and hardware stores, and construction and safety supply distributors. For the outlet nearest you, call 800-245-1191 or email info@dumondglobal.com.

Cost will vary depending upon type and conditions to be stripped, but in most cases a single application will do the complete removal job. This product has an average coverage rate of about 200 sq. ft/gallon. Coverage may be greater or less depending upon surface conditions.

LIMITED WARRANTY:

The manufacturer and distributors liability under any express or implied warranty is limited solely to replacement of product that is defective or refund of the purchase price. Claims must be made within one year of purchase and be accompanied with proof of purchase. The manufacturer and distributors shall not be liable for injury, labor or any consequential damages.

TECHNICAL SERVICES:

Dumond's expert staff is available to answer technical questions and provide product-specific information required by architects, specifiers, contractors and property owners. Expert, on-site assistance is available at no additional cost. Call 800-245-1191 or email info@dumondglobal.com with product or technical questions.

TECHNICAL DATA:

Form:	White Liquid
Flashpoint:	146° F (closed cup)
WT/Gal:	10.0 Lbs
Ph:	Neutral