

Peel Away®: Black Mastic Remover - 0777

- Product Description & Use:** Black Mastic Remover is a low odor mastic remover with superior performance when it comes to removing all types of mastics, adhesives, pastes and glues. It contains a unique blend of surfactants, which allows for low surface tension, making this formulation the most rinsible and residue free mastic remover on the market today. Black Mastic Remover contains no hazardous citrus or chlorinated solvents.
- Limitations:** This product is most effective when temperatures are above 50° F.
- Test Patch:** Before starting a project, it is important that a small test area be done typical of the surface to be removed.
- Application & Spread Rate:** Apply manually or with a garden sprayer to small areas, and take up as much material as quickly as possible to prevent excess penetration into the substrate. Allow as little time as necessary to let Black Mastic Remover to penetrate and soften the adhesive. Using a stiff bristled brush or squeegee, clean up liquefied mastic and dispose of properly (check with local authorities for proper regulations). Be sure not to let the Black Mastic Remover to come into contact with any areas which may absorb solvents such as drywall, woodwork, drains, etc. Be sure to cover and dike these areas carefully. Aggressively clean the surface with water and detergent before applying any new mastic. Pressure washers with wet vacs can be used to do the final rinse and will ensure a clean surface.
- Availability & Cost:** All PEEL AWAY® products are available through a network of product distributors and paint stores. Call Dumond Chemicals (609-655-7700) for the nearest distributor.
Cost will vary depending upon type and conditions of coatings and surface. The PEEL AWAY® 2 product has an average coverage of about 30 to 70 square feet per gallon. The average cost can be calculated by dividing the price per gallon cost (obtained from local distributor) by the average square footage.
- Health & Safety Requirements: COMBUSTABLE:** Keep away from sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing in mist. Use with adequate ventilation. Wash thoroughly after using. Keep container closed. Use a NIOSH approved respirator with organic vapor cartridge. Use chemical goggles. Wear rubber or neoprene gloves. Adhere to all OSHA and EPA regulations when using this product.
Ingestion: Do not induce vomiting. Get medical attention immediately. **Inhalation:** Move victim to fresh air. If necessary, support breathing. If breathing does not return to normal within a few minutes, seek immediate medical attention. **Eye Contact:** Immediately flush with clean water for 20-30 minutes. Obtain emergency medical attention. **Skin Contact:** Wash with soap and water. If irritation persists seek immediate medical attention.

7. **Warranty:** Dumond Chemicals, Inc. warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. Dumond Chemicals, Inc. liability shall be limited in all events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. Dumond Chemicals, Inc. shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of Dumond Chemicals, Inc. or its distributors, and dealers.

8. **Technical Services:** Dumond's expert staff is available to answer technical questions and provide product-specific information required by architects, specifiers, contractors and property owners. Expert, on-site assistance is available at no additional cost. Call 800-245-1191 or email info@dumondglobal.com with product or technical questions.

Technical Data

Appearance:	Clear Liquid
Odor:	Low
Boiling Point:	>300°
Vapor Density:	Heavier Than Air
pH:	Neutral
Flash Point:	149° F
Weight:	5 Gal. Pail – 35lbs.