

Peel Away® Marine Strip II: A Revolutionary Concept in Marine Paint Removal

- Product Description & Use:** PEEL AWAY® Marine Strip II is specifically designed as an alternative to PEEL AWAY Marine Safety Strip for removing antifouling paint where the epoxy barrier coat is to be left intact. This product is an alkaline paste and in a single application will remove all antifouling coatings and there are NO TOXIC FUMES AND NO FLAMMABLE SOLVENTS. The system includes a paste that is troweled or sprayed over the surface to be stripped. This paste is then covered with a fibrous laminated cloth which controls evaporation and is left on until all of the paint is dissolved. The laminated cloth is then removed with the bulk of the paste and coatings adhering to it and the stripped surface is then washed clean with water. Surface should then be neutralized.
- Advantages:** No special ventilation needed. Does not contain methylene chloride, MEK or any other highly flammable solvent. Easily clings to a vertical or overhang surface.
- Limitations:** Product efficiency is reduced below a temperature of 40°F. It will not work on any chemically resistant coatings, ie: epoxies, urethanes, etc. DO NOT USE ON ALUMINUM.
- Test Patch:** It is often impossible to know the type or condition of the surface before paint is removed. Before a project is started it is important that a small test area be done typical of the surface to be stripped to ensure that the results will be satisfactory.
- General Application:** Apply paste about 1/8" thick with either trowel or special spray equipment. Cover paste with special PEEL AWAY fibrous laminated cloth printed side facing out. Usual time frame for removal of multiple layers of paint is 24 hours. Remove by sliding putty knife or tool under paste around the outside edges of the paper easing paint/paste away from the surface in one piece. Collect and put into plastic bags and dispose of in compliance with local regulations. Surface can now be washed down using a hose and a small nylon scrub brush. Surface should be neutralized with vinegar or power washed with water.
- Availability & Cost:** All PEEL AWAY® products are available through a network of product distributors. Call Dumond Chemicals (609-655-7700) for the nearest distributor.
Cost: Cost will vary depending upon type and conditions to be stripped and number of layers to be removed. PEEL AWAY® has an average coverage of about 20 sq. feet per gallon. The average cost can be calculated by dividing the gallon cost (obtain from local distributor) by the average square feet coverage.
- Warranty:** Dumond Chemicals, Inc. warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. Dumond Chemicals, Inc. liability shall be limited in all events

to supplying sufficient products to re-treat the specific areas to which defective product has been applied. Dumond Chemicals, Inc. shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of Dumond Chemicals, Inc. or its distributors, and dealers.

Technical Data

Form:	Paste
Viscosity:	26.5
Wt./Gal.:	12 pounds
Flash Point:	None
VOC:	0
pH:	13.0

12. **Technical Services:** Dumond's expert staff is available to answer technical questions and provide product-specific information required by architects, specifiers, contractors and property owners at 800-245-1191. Product Specification & Data Pages and MSDS can be accessed from our website at www.dumondchemicals.com.