

SAFETY DATA SHEET
DUMOND PEEL AWAY BLACK MASTIC
REMOVER

1. Product and Company Identification

Product Code: 00044D
Product Name: DUMOND PEEL AWAY BLACK MASTIC REMOVER
Company Name: DUMOND CHEMICALS **Phone Number:**
1475 PHOENIXVILLE PIKE (800)245-1191
Suite 18
WEST CHESTER, PA 19380
Web site address: www.dumondchemicals.com
Emergency Contact: InfoTrac # 79363 (800)457-4280
Information: Sales& information (800)245-1191

2. Hazards Identification

Acute Toxicity: Skin, Category 4
Skin Corrosion/Irritation, Category 2
Aspiration Toxicity, Category 2
Acute Toxicity: Inhalation, Category 4
Flammable Liquids, Category 4



GHS Signal Word: **Warning**

GHS Hazard Phrases: H227 - Combustible liquid.
H305 - May be harmful if swallowed and enters airways.
H312 - Harmful in contact with skin.
H315 - Causes skin irritation.
H332 - Harmful if inhaled.

GHS Precaution Phrases: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection.

GHS Response Phrases: P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P321 - Specific treatment see appropriate section on the label or SDS.
P331 - Do NOT induce vomiting.
P332+313 - If skin irritation occurs, get medical advice/attention.
P362 - Take off contaminated clothing and wash before re-use.
P363 - Wash contaminated clothing before reuse.

GHS Storage and Disposal Phrases: P403+235 - Store in cool/well-ventilated place.
P405 - Store locked up.
P501 - Dispose of contents/container to a waste facility according to local regulations.

SAFETY DATA SHEET
DUMOND PEEL AWAY BLACK MASTIC
REMOVER

**Potential Health Effects
(Acute and Chronic):**

Prolonged or repeated skin contact may cause defatting and dermatitis.

Chronic: May cause liver and kidney damage. Sophisticated modeling has clearly proven that 2-butoxyethanol does not build up in the body under any kinds of normal use.

Inhalation:

Harmful if inhaled. May cause narcotic effects in high concentration. May cause lung damage. May cause anemia. May cause central nervous system effects such as nausea and headache. Material is irritating to mucous membranes and upper respiratory tract.

Skin Contact:

May cause irritation with burning pain, itching and redness. Causes skin irritation. Causes symptoms similar to those of inhalation. Skin sensitization testing with human volunteers produced negative results. A skin notation is not recommended by ACGIH, based on estimates from physiologically based pharmacokinetic models which indicate that, even in worst-case dermal-exposure scenarios, 2-butoxyethanol is not absorbed in amounts sufficient to cause red blood cell hemolysis in humans. May cause skin irritation.

Eye Contact:

Causes redness and pain. Causes severe eye irritation.

Ingestion:

Aspiration hazard. May cause irritation of the digestive tract. Harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Prolonged or repeated exposure may cause allergic reactions in certain sensitive individuals.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
64742-47-8	Hydrotreated light distillate (petroleum)	<95.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	< 7.0 %
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	< 5.0 %

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation:

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Get medical aid immediately. Remove from exposure and move to fresh air immediately.

In Case of Skin Contact:

In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

In Case of Eye Contact:

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion:

Potential for aspiration if swallowed. Get medical aid immediately. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Call a poison control center. If swallowed, wash out mouth with water provided person is conscious. Call a physician.

Signs and Symptoms Of Exposure:

Exposure can cause: Nausea, headache, and vomiting. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Note to Physician:

None known.

SAFETY DATA SHEET
DUMOND PEEL AWAY BLACK MASTIC
REMOVER

5. Fire Fighting Measures

Flash Pt:	> 141.00 F Method Used: Cleveland Closed Cup
Explosive Limits:	LEL: No data. UEL: No data.
Autoignition Pt:	No data.
Suitable Extinguishing Media:	Use water spray, dry chemical, carbon dioxide, or appropriate foam. Suitable:
Fire Fighting Instructions:	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Will burn if involved in a fire. Combustible liquid and vapor. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s):
Flammable Properties and Hazards:	No data available.
Hazardous Combustion Products:	No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:	Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Provide ventilation. Wear a self contained breathing apparatus and appropriate personal protection. (See Exposure Controls, Personal Protection section). Use a spark-proof tool. Do not let this chemical enter the environment. PROCEDURE(S) OF PERSONAL PRECAUTION(S) Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves. Methods for cleaning up. Ventilate area and wash spill site after material pickup is complete.
---	---

7. Handling and Storage

Precautions To Be Taken in Handling:	Wash thoroughly after handling. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Keep away from heat and flame. Use spark-proof tools and explosion proof equipment. Do not ingest or inhale. Use only in a chemical fume hood. User Exposure: Do not breathe vapor.
Precautions To Be Taken in Storing:	Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Store in a cool, dry place. Suitable:

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
64742-47-8	Hydrotreated light distillate (petroleum)	No data.	TLV: 200 mg/m3	No data.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	PEL: 50 ppm	TLV: 20 ppm	No data.
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	No data.	No data.	No data.

SAFETY DATA SHEET
DUMOND PEEL AWAY BLACK MASTIC
REMOVER

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability: ignition sources, Incompatible materials.

Incompatibility - Materials To Avoid: Strong acids. Strong bases, Aluminum.

Hazardous Decomposition or Byproducts: Nitrogen oxides, Carbon monoxide, oxides of sulfur.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions: No data available.

11. Toxicological Information

Toxicological Information: Epidemiology: No information found.
Teratogenicity: No information available. Reproductive Effects: Mutagenicity:
Neurotoxicity:

Carcinogenicity/Other Information: CAS# 64742-47-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 111-76-2:
ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans.
California: Not listed.
NTP: Not listed.
IARC: Not listed.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	n.a.	3	A3	n.a.
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information: Environmental: TERRESTRIAL FATE: Based on a recommended classification scheme, an estimated Koc value of 67,, determined from an experimental log Kow and a recommended regression-derived equation, indicates that ethylene glycol mono-n-butyl ether is expected to have high mobility in soil. An estimated BCF value of 2.5 was calculated for ethylene glycol mono-n-butyl ether, using an experimental log Kow of 0.83 and a recommended regression-derived equation. According to a recommended classification scheme, this BCF value suggests that bioconcentration in aquatic organisms is low.

Physical: No information found.

Other: An estimated BCF value of 2.5,, from an experimental log Kow, suggests that ethylene glycol mono-n-butyl ether bioconcentration in aquatic organisms will be low, according to a recommended classification scheme. ELIMINATION.

SAFETY DATA SHEET
DUMOND PEEL AWAY BLACK MASTIC
REMOVER

13. Disposal Considerations

Waste Disposal Method: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.
RCRA P-Series: None listed.
RCRA U-Series: None listed. Empty container may be recycled or disposed of as solid sanitary waste. Do not reuse container. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s
(applies to single containers of more than 119 gallons - smaller containers are not regulated)

DOT Hazard Class:

UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Environmentally hazardous substance, liquid, n.o.s
(applies to single containers of more than 119 gallons - smaller containers are not regulated)

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	No	No	Yes-Cat. N230
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Glycol Ether EB}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
9016-45-9	Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydr {Nonylphenol Ethoxylate}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 5A(2), 8A PAIR, 12(b); CA PROP.65: No

SAFETY DATA SHEET
DUMOND PEEL AWAY BLACK MASTIC
REMOVER

16. Other Information

Revision Date: 10/10/2016

Additional Information About This Product: No data available.

This Product:

Company Policy or

Disclaimer:

THE INFORMATION CONTAINED HEREIN is based upon available information at the time of preparation and is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that the information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or any other user proximately caused by the material if misused or if reasonable safety procedures are not adheared to as stipulated in the data sheet and on the product label. Furthermore, vendor assumes no responsibility for injury or damage caused by abnormal use of this material even if reasonable safety measures are followed.