

## 2180 / 2185 • For Decks, Siding & Fencing

**Product Description & Use:** **Peel Away**® Deck Cleaner is a concentrated and safe maintenance cleaner for exterior use on wood decking, siding, shakes and outdoor furniture. **Peel Away**® Deck Cleaner is also recommended for composite decking, concrete, stucco, vinyl siding, fiberglass and most outdoor furniture. **This product is available in Gallons and 5 Gallon Pails.**

**Limitations:** Product efficiency is greatly reduced when air and surface temperature is below 50° F.

**Test Area:** Test an inconspicuous area and allow drying thoroughly before general use.

**Coverage:** This product can be diluted at a ratio of **7:1** and will cover between 1,600 and 2,400 square feet per gallon.

**Application:** To clean, brighten, and remove mold, mildew, and algae from wood siding, decks, and fences. Also recommended on concrete, brick, stucco, vinyl, fiberglass and most outdoor furniture.

1. Apply diluted solution (see above for dilution) liberally with a plastic, pump style garden sprayer. On vertical surfaces, start from the bottom and work up. **DO NOT APPLY TO HOT SURFACES OR IN DIRECT SUNLIGHT.**

2. Agitate surface with a stiff brush or power washer. **NOTE:** To avoid surface damage, if using a power washer, **DO NOT EXCEED 1000 PSI OR A 40 DEGREE TIP.** After surface is cleaned, thoroughly rinse surface and allow drying. Additional application may be necessary for desired results.

3. Allow surface to dry thoroughly before applying a new finish. Lightly sanding the surface will help with penetration and adhesion of the new coatings.

**Dilution Guide:** **DILUTE WITH 7 GALLONS OF WATER TO 1 GALLON OF CLEANER.** A power washer's chemical injector will automatically reduce this product at a 7 to 1 ration and does not need to be diluted before inserting

chemical injector into the container.

**Health & Safety: CAUTION:** Wear safety goggles and/or face shield. Wear butyl gloves, impervious apron, boots and other clothing are recommended if needed, to prevent contact. If spraying (only outdoors), use a NIOSH approved organic vapor/dust mist respirator with appropriate eye protection. Do not mix or use with other household cleaners or chemicals. All surfaces must be thoroughly rinsed, dry and neutralized prior to staining or coating. Stripper residue will adversely affect stain or coating. Exercise caution when working on surfaces that are wet, especially from stripper. Wet surfaces are extremely slippery.

**DANGER: CORROSIVE LIQUID. KEEP OUT OF REACH OF CHILDREN.** CONTACT WITH EYES MAY CAUSE SEVERE BURNS WITH POSSIBLE CORNEA DAMAGE AND BLINDNESS. SKIN CONTACT MAY CAUSE CHEMICAL BURNS OR DERMATITIS IF EXPOSURE IS PROLONGED. VAPOR OF MIST MAY CAUSE IRRITATION TO EYES, MUCOUS MEMBRANES AND RESPIRATORY TRACT. INGESTION MAY CAUSE GASTROINTESTINAL CORROSION, VOMITTING, DIARRHEA, SHOCK OR DEATH. **Close container after each use. Use with adequate ventilation only. Wash thoroughly with soap and water after each use.**

**Warranty:** Dumond Chemicals, Inc. warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. Dumond Chemicals, Inc. liability shall be limited in all events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. Dumond Chemicals, Inc. shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of Dumond Chemicals, Inc. or its distributors, and dealers.

**Technical Services:** Dumond's expert staff is available to answer technical questions and provide product-specific

information required by architects, specifiers, contractors and property owners. Expert, on-site assistance is available at no additional cost. Call 800-245-1191 or email [info@dumondglobal.com](mailto:info@dumondglobal.com) with product or technical questions.

## Technical Data

<b>Form:</b>	<b>Pale Yellow/Green Liquid</b>
<b>Odor:</b>	<b>Mild Chlorine Odor</b>
<b>Wt. /Gal.:</b>	<b>9.0 lbs</b>
<b>Flash Point:</b>	<b>None</b>
<b>pH:</b>	<b>12</b>