



Peel Away® Deck Restorer

Tech Data Sheet

Product Description & Use: Peel Away® Deck Restorer is a concentrated formula that can be mixed to a 7:1 ratio. This versatile product restores grey, discolored, and weathered wood to its natural color within minutes. Peel Away® Deck Restorer is safe and effective when cleaning and restoring exterior wood substrates to include cedar, redwood, oak, pine, pressure treated and more. This product is ideal for cleaning and restoring weathered wood decks, docks, fences, furniture, siding, shingles and more. Peel Away® Deck Restorer restores wood to its natural appearance without leaving a pale bleached out substrate; effectively removes dirt, grime, moss, mold, mildew, algae, tannin and water stains from wood substrates. This water-based, biodegradable, bleach free formula is user-friendly; easy brush, roll, pump sprayer, or chemical injector application. Peel Away® Deck Restorer is recommended for wood that does not have any visible surface coatings; ideal for surface preparation prior to the application of solid stains, semi-transparent stains, clear finishes and painting.

Features & Benefits:

- Concentrated formula that can be mixed to a 7:1 ratio
- Restores grey, discolored, and weathered wood to its natural color within minutes
- Safe and effective when cleaning and restoring exterior wood substrates to include cedar, redwood, oak, pine, pressure treated and more
- Ideal for cleaning and restoring weathered wood decks, docks, fences, furniture, siding, shingles and more
- Restores wood to its natural appearance without leaving a pale bleached out substrate
- Effectively removes dirt, grime, moss, mold, mildew, algae, tannin and water stains from wood substrates
- Water-based, biodegradable and bleach free formula
- Easy brush, roll, pump sprayer, or chemical injector application
- Recommended for wood that does not have any visible surface coatings; ideal for surface preparation prior to the application of solid stains, semi-transparent stains, clear finishes and painting

Limitations: Peel Away® Deck Restorer is not recommended for the removal of new solid or semi-transparent coatings. For new solid or semi-transparent coatings please use Peel Away®

Deck Stripper. Do not apply product in direct sunlight or allow product to dry to the surface. Product loses all effectiveness when dry.

Test Patch: Always perform a small inconspicuous test area on each type of substrate prior to full application. Testing before beginning any project is the best way to ensure product effectiveness. Test patches can determine the proper dwell time to apply the product for you specific application. Failure to do a test patch can result in need for more than one application, causing increased labor and material costs.

Recommended Substrates: Before applying to an entire substrate always do a test patch. Recommended for use on wood, pine, oak, cedar, redwood and pressure treated decks, siding and fencing.

Regulatory Information: VOC compliance - **Peel Away**[®] Deck Restorer meets all national, state and local regulations.

Preparation: Prepare surface by scraping or pressure washing to remove all loose or peeling coatings. Allow substrate to dry before applying **Peel Away**[®] Deck Restorer. Protect and cover all areas, vegetation and surfaces not designated to be stripped including adjoining surfaces where overspray may travel. Solvent resistant polyethylene sheets can be used as an effective barrier. Wet down all vegetation and cover with **Dumond**[®] **Catch-N-Cover**[™] or 6 mil solvent resistant polyethylene sheets.

Surface and Air Temperatures: To avoid product from freezing and reducing effectiveness do not use below 35° degrees Fahrenheit. For best results, use product in temperatures above 50° degrees Fahrenheit and below 90° degrees Fahrenheit. Product effectiveness is increased in warmer temperatures. Avoid working in direct sunlight and do not allow product to dry to the surface. Working in smaller more manageable areas is encouraged. Product loses all effectiveness when dry.

Application & Spread Rate: **Dumond**[®] **Chemicals** always recommends working in smaller manageable areas when striping unless you are working with many people, only restore what you can rinse before the restorer dries. Apply **Peel Away**[®] Deck Restorer to the surface with a pump style sprayer, when working on vertical surfaces always apply product from the bottom up to avoid streaking. Allow Restorer to dwell 15- 30 min based on your previous test area. Do not allow product to dry to the surface. **Peel Away**[®] Deck Restorer has an average coverage rate of 200-300 Sq. Ft. Per. Gallon.

- **Dilution Guide:** This Product can be diluted up to a 7:1 ratio, when diluted coverage rate would be 1,600- 2,400 Sq. Ft. Per. Gallon. A power washer's chemicals injector will automatically reduce this product to a 7:1 ratio and does not need to be diluted before inserting chemical injector into the container.

Spray Application: Low pressure pump style sprayer

Removal & Clean Up: Agitate surface with a stiff brush or power wash to restore the surface to its original beauty. After the surface is restored, thoroughly rinse surface; Additional application may be necessary if not all the coatings have been removed from the surface. Allow surface to dry for 2-3 days and then apply **Peel Away®** Deck Brightener/Neutralizer.

Best Practices:

- Always test patch each type of surface and coatings for efficacy, dwell times, and thickness
- If product dries to the surface mist with water and re-apply stripper
- Product loses all effectiveness when dry
- To avoid surface damage when using a pressure washer do not exceed 3000 PSI or a 40 degree tip
- Always follow with **Peel Away®** Deck Brightener/Neutralizer 2-3 days after removal is complete, before re-coating.
- For thin coatings, **Peel Away®** Deck Restorer can be diluted up to a 7:1 ratio with water
- If **Peel Away®** Deck Brightener/Neutralizer is not used, the high pH of the surface may cause premature failure of any future coatings.

Availability & Cost: **Dumond® Chemicals** products are available through a nationwide network of paint stores, hardware stores and safety supply distributors. For outlet nearest you please visit www.dumondchemicals.com once on the website type your zip code or postal code into the dealer locator to find addresses and phone numbers of your nearest dealer.

Health & Safety Requirements: Not for internal consumption. While **Peel Away®** Deck Restorer is formulated to be safe for the user, surface and environment, proper safety procedures should be followed always when handling this product. Read the full label and MSDS for precautionary instructions before use.

24-Hour Emergency Information:

1-800-535-5053 **North America** or 1-325-323-3500 **International**

Warranty: **Dumond® Chemicals, Inc.** warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. **Dumond® Chemicals, Inc.** liability shall be limited in all Events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. **Dumond® Chemicals, Inc.** shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of **Dumond® Chemicals, Inc.** or its distributors, and dealers.

Technical Services: Dumond's expert staff is available to answer technical questions and provide product-specific information. On-site assistance is available at no additional cost. Call 800-245-1191, email info@dumondglobal.com or visit www.dumondchemicals.com with product or technical questions.

Technical Data:

- ***Form*** - Liquid
- ***Wt./Gal*** – 10 Lbs.
- ***pH*** - 12
- ***Freeze Point*** – 32 Degrees
- ***Shelf Life*** - 2 Years



1475 Phoenixville Pike, Suite 18 Phone: 609/655-7700 email: info@dumondglobal.com
West Chester, PA 19380 Fax: 609/655-7725 www.dumondchemicals.com