



## Peel Away® Deck Stripper

## Tech Data Sheet

**Product Description & Use:** Peel Away® Deck Stripper is a ready-to-use deck stripper that is formulated for all wood substrates. This product effectively removes oil and water-based solid stains, semi-transparent stains, clear finishes, weathered latex and varnish from pine, oak, cedar, redwood and pressured treated decks, docks, fences, furniture and siding. Peel Away® Deck Stripper restores wood to its natural appearance; cleans and restores grey and weathered wood surfaces to its natural color without leaving a pale bleached out substrate. This product also removes mildew, tannin, water stains, dirt, mill glaze and stains caused by mold and mildew; resulting in a clean, like-new wood surface. Peel Away® Deck Stripper is a water-based, biodegradable, bleach free formula that is non-flammable and contains no harmful odors or fumes. This product is user-friendly and can be easily applied with a brush, roller, or pump sprayer.

### **Features & Benefits:**

- Ready-to-use deck stripper is formulated for all wood substrates
- Effectively removes oil and water-based solid stains, semi-transparent stains, clear finishes, weathered latex and varnish from pine, oak, cedar, redwood and pressured treated decks, docks, fences, furniture and siding
- Restores wood to its natural appearance; this product restores grey and weathered wood to its natural color without leaving a pale bleached out substrate
- Removes mildew, tannin, water stains, dirt, mill glaze and stains caused by mold and mildew; resulting in a clean, like-new wood surface
- Water-based, biodegradable and bleach free formula
- Non-flammable; no harmful odors or fumes
- Easy brush, roll, or pump sprayer application

**Limitations:** Peel Away® Deck Stripper is alkaline and may darken soft woods but should be followed with Peel Away® Deck Brightener/Neutralizer to lighten before recoating. Always do a test patch prior to full paint removal. Do not apply product in direct sunlight or allow product to dry on the surface. Product loses all effectiveness when dry.

**Test Patch:** Always perform a small inconspicuous test area on each type of substrate and paint coating prior to full application. Testing before beginning any project is the best way to ensure

product effectiveness. Test patches can determine the proper dwell time and thickness to apply the product for you specific application. Failure to do a test patch can result in need for more than one application, increasing labor and material costs.

**Recommended Substrates:** Before applying to an entire substrate always do a test patch. Recommended for use on wood substrates such as pine, oak, cedar, redwood and pressure treated decks, siding and fencing.

**Regulatory Information:** VOC compliance - **Peel Away**<sup>®</sup> Deck Stripper meets all national, state and local regulations.

**Preparation:** Prepare surface by scraping or pressure washing to remove all loose or peeling coatings. Allow substrate to dry before applying **Peel Away**<sup>®</sup> Deck Stripper. Protect and cover all areas, vegetation and surfaces not designated to be stripped including adjoining surfaces where overspray may travel. Solvent resistant polyethylene sheets can be used as an effective barrier. Wet down all vegetation and cover with **Dumond**<sup>®</sup> **Catch-N-Cover**<sup>™</sup> or 6 mil solvent resistant polyethylene sheets.

**Surface and Air Temperatures:** To avoid product from freezing and reducing effectiveness do not use below 35° degrees Fahrenheit. For best results, use product in temperatures above 50° degrees Fahrenheit and below 90° degrees Fahrenheit. Product effectiveness is increased in warmer temperatures. Avoid working in direct sunlight and do not allow product to dry to the surface. Working in smaller more manageable areas in encouraged. Product loses all effectiveness when dry. Product loses all effectiveness when dry.

**Application & Spread Rate:** **Dumond**<sup>®</sup> **Chemicals** always recommends working in smaller manageable areas when striping unless you are working with a large number of people, only strip what you can rinse before the remover dries. Apply **Peel Away**<sup>®</sup> Deck Stripper to the surface with a pump sprayer, when working on vertical surfaces always apply product from the bottom up to avoid streaking. Allow stripper to dwell 15- 30 min based on your previous test area. Do not allow product to dry on the surface. **Peel Away**<sup>®</sup> Deck Stripper has an average coverage rate of 100- 125 Sq. Ft. Per. Gallon.

**Spray Application:** Low pressure pump type sprayer

**Removal & Clean Up:** Agitate surface with a stiff brush or power wash to remove coating. After coating is removed, thoroughly rinse surface; Additional application may be necessary if not all of the coatings have been removed from the surface. Allow surface to dry for 2-3 days and then apply **Peel Away**<sup>®</sup> Deck Brightener/Neutralizer allowing for better penetration.

**Best Practices:**

- Always test patch each type of surface and coatings for efficacy, dwell times, and thickness
- If product dries to the surface mist with water and reapply stripper
- Product loses all effectiveness when dry
- To avoid surface damage when using a pressure washer do not exceed 3000 PSI and a 40-degree tip
- Always follow with **Peel Away**® Deck Brightener/Neutralizer 2-3 days after removal is complete, before re-coating.
- For thin coatings, **Peel Away**® Deck Stripper can be diluted up to a 2:1 ratio with water
- If **Peel Away**® Deck Brightener/Neutralizer is not used, the high pH of the surface may cause premature failure of any future coatings.

***Availability & Cost:*** **Dumond**® **Chemicals** products are available through a nationwide network of paint stores, hardware stores and safety supply distributors. For outlet nearest you please visit [www.dumondchemicals.com](http://www.dumondchemicals.com) once on the website type your zip code or postal code into the dealer locator to find addresses and phone numbers of your nearest dealer.

***Health & Safety Requirements:*** Not for internal consumption. While **Peel Away**® Deck Stripper is formulated to be safe for the user, surface and environment, proper safety procedures should be followed always when handling this product. Read the full label and MSDS for precautionary instructions before use.

#### **24-Hour Emergency Information:**

1-800-535-5053 **North America** or 1-325-323-3500 **International**

***Warranty:*** **Dumond**® **Chemicals, Inc.** warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. **Dumond**® **Chemicals, Inc.** liability shall be limited in all Events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. **Dumond**® **Chemicals, Inc.** shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of **Dumond**® **Chemicals, Inc.** or its distributors, and dealers.

***Technical Services:*** **Dumond**'s expert staff is available to answer technical questions and provide product-specific information. On-site assistance is available at no additional cost. Call 800-245-1191, email [info@dumondglobal.com](mailto:info@dumondglobal.com) or visit [www.dumondchemicals.com](http://www.dumondchemicals.com) with product or technical questions.

**Technical Data:**

- **Form** - Liquid
- **Wt./Gal** – 10 lbs.
- **pH** - 12
- **Freeze Point** – 32 degrees
- **Shelf Life** - 2 years



1475 Phoenixville Pike, Suite 18 Phone: 609/655-7700 email: [info@dumondglobal.com](mailto:info@dumondglobal.com)  
West Chester, PA 19380 Fax: 609/655-7725 [www.dumondchemicals.com](http://www.dumondchemicals.com)