



Safe n Easy® Heavy Duty Restoration Cleaner

Tech Data Sheet

Product Description & Use: Safe 'n Easy® Heavy-Duty Masonry Restoration Cleaner is a ready-to-use formulation specifically for extreme atmospheric dirt and staining. This product delivers maximum speed and performance when cleaning a wide variety of unpolished masonry substrates. Safe 'n Easy® Heavy-Duty Masonry Restoration Cleaner is low odor, biodegradable, bleach free and more effective than conventional muriatic and hydrofluoric formulations. This user-friendly cleaner can be applied by a pump sprayer, brush, or roller and is ideal when performing masonry preservation and restoration projects. Safe 'n Easy® Heavy-Duty Masonry Restoration Cleaner cleans without pitting, frosting or altering the surface texture and restores the substrate to its natural appearance.

Features & Benefits:

- Ready-to-use formulation specifically for extreme atmospheric dirt and staining
- Maximum speed and performance when cleaning a wide variety of unpolished masonry substrates
- Safer and more effective than conventional muriatic and hydrofluoric formulations
- Low odor, biodegradable and bleach free
- User-friendly; can be applied by pump sprayer, brush, or roller
- Ideal for masonry preservation and restoration projects
- Cleans without pitting, frosting or altering the surface texture
- Recommended to be used with a pressure washer
- Restores substrate to its natural appearance

Limitations: Safe n Easy® Heavy Duty Restoration Cleaner can be used on the following masonry surfaces: brick, masonry, non-polished marble and granite, limestone, sandstone, bluestone, flagstone, travertine and most other masonry surfaces after testing is done. Safe n Easy® Heavy Duty Restoration Cleaner should be used in temperatures between 40° and 95° Fahrenheit. Not recommended for the use on copper, zinc, aluminum, drywall, plywood, wood surfaces, gypsum, veneer, and most plastics.

Test Patch: Always prepare a test area on each type of surface. Testing before beginning the project is the best way to ensure product suitability and efficacy. This will also teach the user how to handle the product, gauge how to apply, and, determine how long it must remain in

place (dwell time) before removing. Applying incorrectly, or, removing too quickly, may result in the need for more than one application, increasing your labor and material costs.

Recommended Substrates: **Safe n Easy® Heavy Duty Restoration Cleaner** can be used on the following masonry surfaces: brick, masonry, limestone, sandstone, flagstone, concrete pavers, travertine and most other non-polished masonry surfaces after testing is done.

Preparation: Cover and protect areas where cleaning is not desired, including adjoining surfaces where overspray may travel; keep protection in place during removal process. Polyethylene plastic and masking tape create an effective barrier. Nearby plants and other foliage should be covered during application and removal. On hot and humid days, or when working in direct sunlight, dampen the surfaces with water prior to applying **Safe n Easy® Heavy Duty Restoration Cleaner** to keep the product from evaporating too quickly.

Surface and Air Temperatures: To avoid product from freezing and reducing effectiveness do not use below 40° degrees Fahrenheit. For best results, use product in temperatures above 50° degrees Fahrenheit and below 90° degrees Fahrenheit. Product effectiveness is increased in warmer temperatures.

Application & Spread Rate: Apply **Safe n Easy® Heavy Duty Restoration Cleaner** with a pump-up sprayer or trigger spray bottle. It is important to apply bottom to top to avoid any streaking. Leave on for a minimum of 15 – 30 minutes or the time determined during testing, depending on the contaminants present agitate with a nylon bristle brush if necessary. **Safe n Easy® Heavy Duty Restoration Cleaner** provides an average spread rate of about 200 - 250 sq. ft. per gallon; results may vary. **Dumond Chemicals** recommends working in smaller manageable areas that can be rinsed before the product can dry to the surface.

Spray Application: Low pressure sprayer or garden sprayer recommended.

Removal & Clean Up: Remove **Safe n Easy® Heavy Duty Restoration Cleaner** by either high pressure washing, a minimum of 1500 PSI, or using a scrub brush to agitate the surface then rinsing with a hose. Thoroughly wash the surface, from top to bottom again to avoid any streaking, until the foaming action stops to remove all remaining product. Before beginning, especially when power washing, use polyethylene plastic to protect adjacent surfaces from splash back and run down. Collect material removed and dispose of in compliance with Federal, State and local regulations. Allow surface to dry completely before re-coating. Rinse with water from top to bottom again to avoid any streaking.

Best Practices:

- Always test patch each type of surface for efficacy and dwell times.

- Always apply **Safe n Easy® Heavy Duty Restoration Cleaner** from bottom to top and rinse from top to bottom to avoid streaking.
- Do not work in large areas and allow product to dry to the surface before you can rinse it off.

Availability & Cost: **Dumond® Chemicals** products are available through a nationwide network of paint stores, hardware stores and safety supply distributors. For outlet nearest you please visit www.dumondchemicals.com once on the website type your zip code or postal code into the dealer locator to find addresses and phone numbers of your nearest dealer.

Regulatory Information: **Safety, health, and environmental regulations specific for the product in question.**

CERCLA Hazardous Substances (Section 103)/RQ: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Potassium Hydroxide (5% maximum) of 1,000 lbs., is 20,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA SARA 302: This product does not contain chemicals regulated under SARA Section 302.

EPA SARA 311 Hazard Classification: Acute health, chronic health.

EPA SARA 313: This product does not contain chemicals regulated under SARA Section 313.

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory.

California Proposition 65: This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

Canadian Environmental Protection Act: All of the components of this product are listed on the Canadian Domestic Substances List (DSL).

Dispose in accordance with all local, state and federal regulations.

Health & Safety Requirements: Not for internal consumption. While **Safe n Easy® Heavy Duty Restoration Cleaner** is formulated to be safe for the user, surface and environment, proper safety procedures should be followed at all times when handling this product. Read the full label and MSDS for precautionary instructions before use.

24-Hour Emergency Information:

1-800-535-5053 **North America** or 1-325-323-3500 **International**

Warranty: **Dumond® Chemicals, Inc.** warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. **Dumond® Chemicals, Inc.** liability shall be limited in all

Events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. **Dumond® Chemicals, Inc.** shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of **Dumond® Chemicals, Inc.** or its distributors, and dealers.

Technical Services: Dumond's expert staff is available to answer technical questions and provide product-specific information. On-site assistance is available at no additional cost. Call 800-245-1191, email info@dumondglobal.com or visit www.dumondchemicals.com with product or technical questions.

Technical Data:

- **Form** – Clear Liquid
- **Wt. /Gal** – 10 lbs.
- **pH** – 1.5
- **Freeze Point** – 32 degrees
- **Shelf Life** – 3 years



1475 Phoenixville Pike, Suite 18 Phone: 609/655-7700 email: info@dumondglobal.com
West Chester, PA 19380 Fax: 609/655-7725 www.dumondchemicals.com