



Wipe Out - Porous Surface Graffiti Remover

Tech Data Sheet

Product Description & Use: Watch Dog™ Wipe Out Porous Surface Graffiti Remover easily and effectively removes graffiti from porous and unpainted masonry substrates. This innovative formula delivers maximum speed and performance without surface damage. **Watch Dog™ Wipe Out Porous Surface Graffiti Remover** is a non-flammable, non-drip gel, environmentally friendly formulation that dissolves graffiti within 15-30 minutes. **Wipe Out Porous Surface Graffiti Remover** is ideal for historic stone and restoration; salvaging the substrate and avoiding traditional damages from scraping, grinding and various blasting techniques. For best results, remove with a pressure washer; use an oscillating tip and low pressure. If a water or power source is not available, a compressor and airless paint sprayer can be used. Alternatively, use a nylon scrub brush to agitate the surface, then rinse with a spray bottle.

Features & Benefits:

- Easily and effectively removes graffiti from porous/unpainted masonry substrates
- Maximum speed and performance without surface damage
- Dissolves graffiti in 15-30 minutes
- Easy brush or roll application; water-rinsible
- Non-flammable, environmentally friendly; non-drip gel formulation for better cling
- Salvages the substrate and avoids traditional damage from scraping, grinding and various blasting techniques

Limitations: Not recommended for use on aluminum, Plexiglas, fiberglass, most plastics, brownstone, limestone, sandstone, plywood and drywall. Not recommended to be used on previously painted or stained surfaces. Not recommended for use in temperatures below 40° degree Fahrenheit. Always do a test patch prior to full removal.

Test Patch: Always perform a small inconspicuous test area on each type of substrate and paint coating prior to full application. Testing before beginning any project is the best way to ensure product effectiveness. Test patches can determine the proper dwell time and thickness to apply the product for you specific application. Failure to do a test patch can result in need for more than one application, increasing labor and material costs.

Recommended Substrates: Before applying to the entire substrate always do a test patch. Recommended for use on concrete, cement, stucco, brick, bare wood and asphalt surfaces that are previously unpainted or stained.

Regulatory Information: VOC compliance - **Watch Dog™ Wipe Out Porous Graffiti Remover** meets all national, state and local regulations.

Preparation: Make sure surface is clean, dry and free from any debris.

Surface and Air Temperatures: To avoid product from freezing and reducing effectiveness do not use below 40° degrees Fahrenheit. For best results, use product in temperatures above 50° degrees Fahrenheit and below 90° degrees Fahrenheit. Product effectiveness is increased in warmer temperatures.

Application & Spread Rate: Apply product liberally, at full strength using a brush or roller. Allow product to remain on surface for up to 30 minutes or more based on your test patch results. Product may require some agitation with a nylon bristled brush. **Watch Dog™ Wipe Out Porous Graffiti Remover** provides an average spread rate of approximately 100-150 sq. ft. per. Gallon. Results may vary based on the substrate texture and porosity.

Spray Application: Not recommended to be airless sprayed.

Removal & Clean Up: Power wash or rinse product from the surface with a garden hose. When power washing substrate use lower pressures, 1000 psi or less, as to not damage your surface. Dispose of water and waste according to federal, state and local regulations.

Best Practices:

- Always test each type of surface and coating for efficacy, dwell times may vary.
- Do not let product dwell over 30 min.
- Do not let the product dry on the surface.
- **Watch Dog™ Wipe Out Porous Graffiti Remover** may darken woods and require neutralization with our **Citri-Lize™**.

Availability & Cost: **Dumond® Chemicals** products are available through a nationwide network of paint stores, hardware stores and safety supply distributors. For outlet nearest you please visit www.dumondchemicals.com once on the website type your zip code or postal code into the dealer locator to find addresses and phone numbers of your nearest dealer.

Health & Safety Requirements: Not for internal consumption. While **Watch Dog™ Wipe Out Porous Graffiti Remover** is formulated to be safe for the user, surface and environment, proper

safety procedures should be followed always when handling this product. Read the full label and MSDS for precautionary instructions before use.

24-Hour Emergency Information:

1-800-535-5053 **North America** or 1-325-323-3500 **International**

Warranty: Dumond® Chemicals, Inc. warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. Dumond® Chemicals, Inc. liability shall be limited in all Events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. Dumond® Chemicals, Inc. shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of Dumond® Chemicals, Inc. or its distributors, and dealers.

Technical Services: Dumond's expert staff is available to answer technical questions and provide product-specific information. On-site assistance is available at no additional cost. Call 800-245-1191, email info@dumondglobal.com or visit www.dumondchemicals.com with product or technical questions.

Technical Data:

- **Form** - Amber Gel
- **Wt./Gal** – 8.9 lb./gal
- **Flash Point** – over 200
- **pH** - 11
- **VOC** – 5%
- **Freeze Point** - 32° F
- **Shelf Life** – 3 years



1475 Phoenixville Pike, Suite 18 Phone: 609/655-7700 email: info@dumondglobal.com
West Chester, PA 19380 Fax: 609/655-7725 www.dumondchemicals.com